715-1-060 CIP (Sheet 1 of 23)

Compressive Strength of Fly Ash Mortar (M8F9525)






Figure 1

60

明 書からいます ひという ようという あまる

Compressive Strength of Fly Ash Mortar 715-1-060 CIP (M9F9525) (Sheet 2 of 23)











Figure 4






Compressive Strength (MPa)

715-1-060 CIP (Sheet 6 of 23)

The Dry Grinding Process

The Attritor dry grinding process is achieved in a stationary tank by means of a rotating shaft and arms that agitate the media into a random state of motion of internal porosity called kinematic porosity. In this expanded condition, the media and particles are free to move, collide and impinge upon each other.



Revolving arm hits grinding media

Media moves forward rapidly

Media collides with media, breaking up product particle






Figure 6




Figure 7




Figure 8

715-1-060 CIP (Sheet 9 of 23)

Compressive Strength of Fly Ash Mortar (MOG9525)






Figure 9

Compressive Strength of Fly Ash Mortar 715-1-060 CIP (Sheet 10 of 23)






Compressive Strength (MPa) <u>ვ</u> ဟ ဟ 715-1-060 CIP (Sheet 12 of 23)

Compressive Strength of Control Mortar (CC) ■ Series1 ◆ Series2 ▲ Series3 Age (days) အ

Figure 12


715-1-060 CIP (Sheet 13 of 23)



- BICROTENC IL 88 PARTICLE MELLYIBA - PATCARE PARALPH PACA VATRICA C. IL			
Fire 1310 133 - 133	ASTR Farameters Pley Bate: 15 ml/sec Vitramonic Sweet: 10 matte Vitramonic Time: 10 meconda		
	Perconnect: Int. 4		
To fl; Edgroc Seman Ref	Id 12: Fribt Low GOAD Str: 12/1/98 True: 1:18 Chan frierbanger Geometra Sper Chalse dec: 784 Spec Chalse dec: 784 Sper Chalse dec:		

Figure 13

715-1-060 CIP (Sheet 14 of 23)







Figure 14


715-1-060 CIP (Sheet 15 of 23)



- NICHOTAGE ELAS PARTICLE AMALYSES - Percent Panalog Neta Percent Panalog Neta			
	TJLA 29	ANTR Parameters Plow Rate: 15 ml/eec Ultrasonic Power: 18 1 Ultrasonic fine: 18	ratte secon ds
Heas/Pres 4: 1.088 1 - 1 Pars Parsh \$1: 0.088 Pars	# 13: 1:1N	Account Half (10274)	
Id \$1: BSEDCC Distrib. Format: Volume Filter: On Man Funce: A vectoring Transmission: U P 2 Trans Lawer Int: 1.004/1.002/1.004 Praidwall: Disables Above Centeral:	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Tager of Change !	122
1 cap call c. co			

Figure 15


715-1-060 CIP (Sheet 16 of 23)



- BICHTELC LIM MATTICLE MALLYRE - Percent Passing Data Various 5.01			
The life Philipsics and	ANTE Parameters low Rate: 15 ml/sec litrassaic Power: 18 watte litrassaic time: 18 wecomes		
Jean/Pres 1: 0.000 - 1 Param]: 1:	Lot code: MANS 400EM 1/8 CS		
d s1: PSS10C Poleme	Id 12: Wynes LOW LOAD Date: \$1/1/79 Time: \$1:55 Chee Prepayance Loom wre! Support Comments Ide: \$4.1 Chee Comments Ide: \$4.2 Chee Comments Ide: \$4.2 Chee Comments Ide: \$1.2 Chee Chee Chee Chee Chee Chee Chee Che		

Figure 16

715-1-060 CIP (Sheet 17 of 23)







Figure 17

715-1-060 CIP (Sheet 18 of 23)



- Michorald xisa particle arlivers - Percept feasing fets Version 6.81			
	HET SO	ANYE Parameters flow Ente: 15 ml/sec Ultrasmic Power: 48 watts Stramoule five: 18 seconds	
Reas/Pres 6: 1 - 1 Par Param 81: 8.000 Par	4 1:11	Lot code: TCL16 1948.PR 1/8CS	
Id 91: ISSUC Distrib. Format: Volume Filter: 00 Fam fine: 68 seconda Fam Former: Avg of I rung Transmission: 70 Laser [st: 1,005/1,382/1.884 Residuals: 51 public Hove Residual: 38 Relow Residual: 38		14 12: PLTATE Time: 0:58	

Figure 18

DOLUME






Figure 19

715-1-060 CIP (Sheet 20 of 23)








Figure 21

715-1-060 CIP (Sheet 22 of 23)




Figure 22




Figure 23